

BSface600



Product Description:

System Specification

- Elegant design according to the view of human engineering
- 4.3" TFT touch screen, easy operation, fashionable and simple interface
- 6 user-defined function keys
- Infrared optical system enables user identification in dark environment.
- Built-in backup battery support extra 4-5 hours continuous operation if power cut.
- Simple access control function, professional access control function is available
- Built-in GPRS communication makes easier device installation without wiring.
- TCP/IP, WiFi communications
- Web server management software via IE browser
- Extendable scheduled doorbell.
- Combination of facial, fingerprint and RFID identification, solved the localization of single biometric

identification

- Biosecurity VX10.0 fingerprint & facial identification algorithm
- Identification can be worked in spite of beard, glasses, bang and other decks, natural or exaggerated expression could both be identified.

Technical Information

BSFace 600

- Processor: Multi-Bio 600
- Camera: High Definition Infrared Camera
- Display: 4.3" TFT with touch screen
- Storage Capacity:
 - Face:700
 - Fingerprint:10,000
 - Logs:100,000
- Back-up Battery: 2000 mAh
- Communication: TCP/IP, RS232/485, WiFi
- USB-HOST: Two
- T&A functions: Extendable Scheduled-bell, DLST, Self-Inquiry, Work Code, short Message
- A&C function: standard professional access control function
- Optional functions: GPRS, serial printer, Mifare/HID/iClass
- Power Supply: 12V 3A
- Verification Speed: ≤2 sec
- Operating Temperature: 0 °C- 45 °C
- Operating Humidity: 20%-80%